

## Galet de came avec axe CR20-VBUUR-IKO - CR20-VBUUR-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr20-vbuur-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR20-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Sealed type With cover outer ring	Sealed type With cylindrical outer ring							
12.700 ( $\frac{1}{2}$ )			CR 20 VBUUR		137	31.750 ( $\frac{1}{4}$ )	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	$\frac{1}{4}$ -20	15.875 ( $\frac{5}{8}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
20.4 (0.80)	31.750 ( $\frac{1}{4}$ )	7.938 ( $\frac{5}{16}$ )	0.794 ( $\frac{1}{16}$ )	4.792 ( $\frac{3}{16}$ )	3.175 ( $\frac{1}{8}$ )	6.350 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{16}$ )	21.828 ( $\frac{7}{8}$ )	27.7	23.600	31.700

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463760
Diam. intérieur	12.7 mm
Diam. extérieur	31.75 mm
Epaisseur	19.05 mm
Poids	137 g
Conditionnement	-

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE