


## Galet de came avec axe CR22-VBUU-IKO - CR22-VBUU-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr22-vbuu-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR22-VBUU

| Stud dia.<br>mm<br>(inch)    | Identification number                   |   |   |   | Mass<br>(Ref.)<br>g     | D                        | C                        | d <sub>1</sub>           | G<br>UNF          | G <sub>1</sub>                                 |                                      |  |  |
|------------------------------|---|---|---|---|-------------------------|--------------------------|--------------------------|--------------------------|-------------------|--|--------------------------------------|--|--|
|                              | Shield type<br>With cover<br>outer ring | Shield type<br>With cylindrical<br>outer ring | Sealed type<br>With cover<br>outer ring | Sealed type<br>With cylindrical<br>outer ring |                         |                          |                          |                          |                   |  |                                      |  |  |
| 12.700<br>( $\frac{1}{2}$ )  |   |   | CR 22                                   | VBUU  | 160                     | 34.925 ( $\frac{1}{2}$ ) | 19.050 ( $\frac{3}{4}$ ) | 12.700 ( $\frac{1}{2}$ ) | $\frac{1}{4}$ -20 | 15.875 ( $\frac{5}{8}$ )                       |                                      |  |  |
| Boundary dimensions mm(inch) |   |   |   |   |                         |                          |                          |                          |                   | Mounting<br>dimension<br>f<br>Min.<br>mm(inch) | Maximum<br>spinning<br>torque<br>N-m | Basic dynamic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N |
| B<br>max                     | B <sub>2</sub>                          | B <sub>3</sub>                                | C <sub>1</sub>                          | g <sub>1</sub>                                | g <sub>2</sub>          | H                        | r                        |                          |                   |  |                                      |  |  |
| 20.4 (0.80)                  | 31.750 ( $\frac{1}{2}$ )                | 7.938 ( $\frac{5}{16}$ )                      | 0.794 ( $\frac{1}{16}$ )                | 4.792 ( $\frac{3}{4}$ )                       | 3.175 ( $\frac{1}{4}$ ) | 6.350 ( $\frac{1}{4}$ )  | 1.588 ( $\frac{1}{8}$ )  | 21.828 ( $\frac{7}{8}$ ) | 27.7              | 23.600   | 31.700                               |  |  |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3616060463852 |
| Diam. intérieur | 12.7 mm       |
| Diam. extérieur | 34.925 mm     |
| Épaisseur       | 19.05 mm      |
| Poids           | 160 g         |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE