


## Galet de came avec axe CR24-V-IKO - CR24-V-IKO

<https://www.123roulement.ch/roulement-palier/roulement-bille/galet-came-axe/cr24-v-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR-V

Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type With cover With cylindrical outer ring		Sealed type With cover With cylindrical outer ring		$\phi$	D	C	$d_1$	G UNF	$G_1$
15.875 (5/8)	CR 24 V				230	38.100 (1 1/2)	22.225 (7/8)	15.875 (5/8)	7/8-18	18.050 (7/8)

Boundary dimensions: mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating $C_0$ N
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	$\phi_1$	$\phi_2$	r				
22.8 (0.90)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/32)	4.762 (3/8)	3.989 (5/32)	1.588 (1/16)	26.166 (1 1/8)	55.7	28 200	40 100

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463876
Diam. intérieur	15.875 mm
Diam. intérieur	5/8" inch
Diam. extérieur	38.1 mm
Diam. extérieur	1 1/2" inch
Epaisseur	22.225 mm
Epaisseur	7/8" inch
Poids	230 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE