


Roulement à rouleaux NQI25-30-JTEKT - NQI25-30-KOYO

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nqi25-30-koyo>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speed ¹⁾ (min ⁻¹)	Bearing No.
F_w	d	D	B	r_{min}	C_r	C_{10}	Oil lub.	Without inner ring
29	25	38	30	0.3	28.9	54.3	16 000	—
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring					Without inner ring	With inner ring	—	
NQI25/30					27	36		0.085

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482637
Diam. intérieur	25 mm
Diam. extérieur	38 mm
Épaisseur	30 mm
Poids	125 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE