

## Roulement à rouleaux NQ40-15AD-JTEKT - NQ40-15AD-KOYO

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq40-15ad-koyo>

### Machined ring needle roller bearings

$F_w$  29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
40	—	50	15	21.0	35.1	12 000	NQ40/15AD	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
$d_a$	$D_a$	$r_a$		0.063	—			
max.	max.	max.						
—	48	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483023
Diam. intérieur	40 mm
Diam. extérieur	50 mm
Épaisseur	15 mm
Poids	63 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE