


Roulement à rouleaux NQ40-20-JTEKT - NQ40-20-KOYO

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/nq40-20-koyo>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
40	35	50	20	27.2	48.8	12 000	NQ40/20	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d _i	D _i	r _a	0.085	0.129			
	min.	max.	max.					
	37	48	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483030
Diam. intérieur	40 mm
Diam. extérieur	50 mm
Épaisseur	20 mm
Poids	85 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE