


Roulement à rouleaux NA4907UU-JTEKT - NA4907UU-KOYO

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/na4907uu-koyo>

Machined ring needle roller bearings

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	B_1	r (min)	C_r	C_{10}	Oil lub.	Without inner ring
42	35	55	20	21	0.6	29.0	40.9	4 700	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		With inner ring	d_a max.	D_a max.	r_a max.	Without inner ring	With inner ring		
		NA4907UU	39	51	0.6	—	0.173	IRM354221	

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483108
Diam. intérieur	35 mm
Diam. extérieur	55 mm
Épaisseur	20 mm
Poids	173 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE