


Roulement à rouleaux NA6915-JTEKT - NA6915-KOYO

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/na6915-koyo>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|----|-----|----|-------------------------|-----------------|--|--------------------|-------------|-----------|
| F _w | d | D | B | C _r | C ₁₀ | Oil lub. | Without inner ring | | |
| 85 | 75 | 105 | 54 | 135.0 | 283.0 | 5 400 | — | | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NA6915 | | | | 80 | 100 | 1 | 0.866 | 1.44 | IRM758554 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952483955 |
| Diam. intérieur | 75 mm |
| Diam. extérieur | 105 mm |
| Épaisseur | 54 mm |
| Poids | 1440 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE