

Roulement à rouleaux RNA4916-JTEKT - RNA4916-KOYO

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/rouleaux/rna4916-koyo>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-------|-------|-------|-------------------------|-----------------|--|--------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Without inner ring | |
| 90 | 80 | 110 | 30 | 91.6 | 178.0 | 5 100 | RNA4916 | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | | | |
| | d_a | D_a | r_a | 0.540 | 0.819 | IRM809030 | | |
| | max. | max. | max. | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 4549250250545 |
| Diam. intérieur | 90 mm |
| Diam. extérieur | 110 mm |
| Épaisseur | 30 mm |
| Poids | 540 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE