

Butée à aiguilles AZ457320-IKO - AZ457320-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/butee-aiguille/az457320-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings

Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
45	AZ 457320	360	AZK 45739	144	WS 4573	GS 4573	108	

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d ₄ Min.	D ₄ Max.	N	N	rpm
45	73	20	45.05	72.5	9	5.5	1	50	69	69	51	75 700	227 000	5 000

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060465979
Diam. intérieur	45 mm
Diam. extérieur	73 mm
Épaisseur	20 mm
Poids	360 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE