

Rondelle de butée GS220360-IKO - GS220360-IKO

<https://www.123roulement.ch/accessoire/rondelle/rondelle-butee/gs220360-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings

Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
220	AZ 220360S2	24 000	AZK 220360Z0	8 000	WS 220360	GS 220360	8 000

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	F _a (1)	C ₁	C ₂	d ₁ Min.	D ₁ Max.	N	N	rpm
220	360	52	220.15	358	20	16	4	246	343	342	247	943 000	5 520 000	1 000

Notes: ^(*) Minimum allowable value of chamfer dimension r
⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060467447
Diam. intérieur	220 mm
Diam. extérieur	360 mm
Épaisseur	16 mm
Matière	ACIER
Poids	8000 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE