

Rotule SI

SIL8-T-K-DURBAL - DSIL8-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/dsil8-t-k-durbal>


SIL8-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | | measurement [mm] | | | | | | |
|-------------------|------------------|------------------|-----|----|----------------|----------------|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
| SIL 8 T/K | | 8 | M 8 | 12 | 9,00 | 24 | 12,5 | 16 |

| type | measurement [mm] | | h | d ₁ PT | load rating C ₁₀ [N] | weight [kg] |
|----------------|--------------------|----|----|----------------------|---------------------------------------|----------------|
| | l ₁ min | W | | | | |
| SI / SIL 8 T/K | 16 | 14 | 36 | 14 | 12,9 | 0,047 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952489155 |
| Diam. intérieur | 8 mm |
| Diam. extérieur | 24 mm |
| Epaisseur | 12 mm |
| Type | SI |
| Poids | 47 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE