

# Rotule SI

## SIL12-T-K-DURBAL - SIL12-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/sil12-t-k-durbal>


### SIL12-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
	SIL 12 T/K	12	M 12	16	12,00	32	17,5	22

type	measurement [mm]			d <sub>1</sub> PT	load rating C <sub>10</sub> [N]	weight [kg]
	l <sub>1</sub> min	W	h			
SI / SIL 12 T/K	22	19	50	13	24,0	0,100

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489261
Diam. intérieur	12 mm
Diam. extérieur	32 mm
Epaisseur	16 mm
Type	SI
Poids	100 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE