

Rotule SI

SI22-T-K-DURBAL - SI22-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/si22-t-k-durbal>


SI22-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 22 TIK		22	M 22 x 1,5	28	20,00	54	30,0	38

type	measurement [mm]			h	d ₁ PT	load rating C ₀ [N]	weight [kg]
	l ₁ min	W					
SI / SIH 22 TIK	37	32		84	15	68,0	0,540

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489605
Diam. intérieur	22 mm
Diam. intérieur	0.866" inch
Diam. extérieur	54 mm
Diam. extérieur	2.126" inch
Epaisseur	28 mm
Epaisseur	1.102" inch
Type	SI
Poids	540 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE