


Rotule SI
SI35-T-K-DURBAL - SI35-T-K-DURBAL
https://www.123roulement.ch/roulement-palier/rotule/si/si35-t-k-durbal

SI35-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 35 TIK		35	M 36 x 2	43	28,00	81	46,0	58

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₃ min	W	h		
SI / SI35 TIK	56	50	125	16	1,600

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489773
Diam. intérieur	35 mm
Diam. extérieur	81 mm
Epaisseur	43 mm
Type	-
Poids	1600 g
Filetage	-
Lubrification	-
Conditionnement	-
Norme	-

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE