

Rotule SA

SAL8-T-K-DURBAL - SAL8-T-K-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/sa/sal8-t-k-durbal


SAL8-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]		Tragzahlen		weight
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 8 T/K		8	M 8	12	9,00	24
type	l ₁ min	l ₂	h	α [°]	C ₁₀ [kN]	[kg]
SA / SAL 8 T/K	25		42	14	12,9	0,038

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490007
Diam. intérieur	8 mm
Diam. extérieur	24 mm
Epaisseur	12 mm
Type	SA
Poids	38 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	-
Norme	Sans norme

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE