


Rotule SA
SAL20-T-K-DURBAL - SAL20-T-K-DURBAL
<https://www.123roulement.ch/roulement-palier/rotule/sa/sal20-t-k-durbal>

SAL20-T-K

male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Red end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 20 T/K		20	M 20 x 1,5	25	18,00	50

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 20 T/K	45	25	78	14	57,0	0,380

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490243
Diam. intérieur	20 mm
Diam. extérieur	50 mm
Epaisseur	25 mm
Type	SA
Poids	380 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1
Norme	Sans norme

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE