

Rotule SA


SAL25-T-K-DURBAL - SAL25-T-K-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/sa/sal25-t-k-durbal

SAL25-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number		measurement [mm]		Tragzahlen		weight
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 25 T/K		25	M 24 x 2	31	22,00	60
type	l ₁ min	l ₂	h	α [°]	C ₀ [kN]	[kg]
SA / SAL 25 T/K	55	30	94	15	85,0	0,640

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490328
Diam. intérieur	25 mm
Diam. extérieur	60 mm
Epaisseur	31 mm
Type	SA
Poids	640 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE