

Rotule SA

SAL50-T-K-DURBAL - SAL50-T-K-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/sa/sal50-t-k-durbal

SAL50-T-K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

male thread: maintenance free, according to DIN ISO 12240-4, series K

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| SAL 50 T/K | | 50 | M 48 x 2 | 60 | 45,00 | 117 |

| type | measurement [mm] | | h | α [°] | Tragzahlen C ₁₀ [kN] | weight [kg] |
|-----------------|--------------------|----------------|-----|-------|---------------------------------|-------------|
| | l ₁ min | l ₂ | | | | |
| SA / SAL 50 T/K | 105 | 59 | 185 | 12 | | 4,800 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952490496 |
| Diam. intérieur | 50 mm |
| Diam. extérieur | 117 mm |
| Epaisseur | 60 mm |
| Type | SA |
| Poids | 4800 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE