

Rotule SA SSAL16-T-K-DURBAL - SSAL16-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/ssal16-t-k-durbal>

SSAL16-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	d	G	measurement [mm]	B	C1	d2
SSAL 16 T/K			16	M 16		21	15,00	42

type	measurement [mm]			h	alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min					
SSA / SSAL 16 T/K	37	21	66	15		39,0	0,210

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490793
Diam. intérieur	16 mm
Diam. extérieur	42 mm
Épaisseur	21 mm
Type	SA
Poids	210 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE