

Rotule SI

DSSI5-T-K-DURBAL - DSSI5-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/dssi5-t-k-durbal>

DSSI5-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]	
right hand thread	left hand thread	d	G
DSSI 5 T/K		5	M 5
		B	C1
		8	6,00
		d1	d2
		18	8,5
		d3	d4
			11

type	measurement [mm]			α °FS	load rating C ₀ [kN]	weight [g]
	l ₁ min	W	h			
DSSI / DSSIL 5 T/K	10	9	27	13	6,0	0,016

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491059
Diam. intérieur	5 mm
Diam. extérieur	18 mm
Epaisseur	8 mm
Type	SI
Poids	16 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE