

Rotule SI

DSSIL5-T-K-DURBAL - DSSIL5-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/dssil5-t-k-durbal>

DSSIL5-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]	
right hand thread	left hand thread	d	G
DSSIL 5 T/K		5	M 5
		B	C1
		8	6,00
		d1	d2
		18	8,5
		d3	d4
			11

type	measurement [mm]			α °	load rating C ₀ [kN]	weight [g]
	l ₁ min	W	h			
DSSIL / DSSIL 5 T/K	10	9	27	13	6,0	0,016

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491080
Diam. intérieur	5 mm
Diam. extérieur	18 mm
Epaisseur	8 mm
Type	SI
Poids	16 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE