

Rotule SI

DSSI8-T-K-DURBAL - DSSI8-T-K-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/si/dssi8-t-k-durbal

DSSI8-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSI 8 T/K			d	G	B	C1	d1	d2	d3	d4
			8	M 8	12	9,00	24	12,5	16	

type	measurement [mm]			α °	load rating C ₀ (kg)	weight kg
	l ₁ min	W	h			
DSSI / DSSIL 8 T/K	16	14	36	14	12,5	0,047

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491134
Diam. intérieur	8 mm
Diam. intérieur	0.315" inch
Diam. extérieur	24 mm
Diam. extérieur	0.945" inch
Epaisseur	12 mm
Epaisseur	0.472" inch
Type	SI
Poids	47 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE