

Rotule SI

DSSIL10-T-K-DURBAL - DSSIL10-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/dssil10-t-k-durbal>

DSSIL10-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 10 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			10	M 10	14	10,50	28	15,0	19	

type	measurement [mm]				α °	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h	α			
DSSIL / DSSIL 10 T/K	20	17	43	13	18,0	0,077	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491172
Diam. intérieur	10 mm
Diam. extérieur	28 mm
Epaisseur	14 mm
Type	SI
Poids	77 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE