

Rotule SI

SSIL30-T-K-DURBAL - SSIL30-T-K-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/ssil30-t-k-durbal>

SSIL30-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C1	d1	d2	d3	d4
SSIL 30 T/K		30	M 30 x 2	37	25,00	70	40,0	50	

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h	α [°]		
SSI / SSIL 30 T/K	51	41	110	17	114,0	1,100

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491721
Diam. intérieur	30 mm
Diam. extérieur	70 mm
Epaisseur	37 mm
Type	SI
Poids	1100 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE