

Rotule SI

DSIL14-PK-DURBAL - DSIL14-PK-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/dsil14-pk-durbal>

DSIL14-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | d | G | measurement (mm) | | | | |
|-------------------|----|------|------------------|-------|----|------|----|
| right hand thread | 14 | M 14 | 19 | 14,00 | 37 | 20,0 | 25 |
| left hand thread | | | | | | | |
| DSIL 14 PK | | | | | | | |

| type | l ₁ min | measurement (mm) | | | lead rating | weight |
|-------------------------|--------------------|------------------|----|-------|--------------------|--------|
| | | W | h | α [°] | C ₀ (N) | (kg) |
| DSI / DSIL 14 PK | 25 | 22 | 57 | 14 | 31,00 | 0,160 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952492056 |
| Diam. intérieur | 14 mm |
| Diam. extérieur | 37 mm |
| Épaisseur | 19 mm |
| Type | SI |
| Poids | 160 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE