

Rotule SI

DSIL25-PK-DURBAL - DSIL25-PK-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/dsil25-pk-durbal>

DSIL25-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | measurement (mm) |
|-------------------|---------------------------------|
| right hand thread | d G |
| DSIL 25 PK | 25 M 24 x 2 31 22,00 61 33,5 42 |

| type | l ₁ min | W | h | α [°] | load rating C ₀ [kN] | weight [kg] |
|------------------|--------------------|----|----|-------|---------------------------------|-------------|
| DSI / DSIL 25 PK | 42 | 36 | 94 | 15 | 85,00 | 0,720 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952492292 |
| Diam. intérieur | 25 mm |
| Diam. extérieur | 61 mm |
| Épaisseur | 31 mm |
| Type | SI |
| Poids | 720 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE