

Rotule GE GAR40-UK-2RS-DURBAL - GAR40-UK-2RS-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/ge/gar40-uk-2rs-durbal>


GAR40-UK-2RS



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C ₁	d ₂
GAR 40 UK-2RS	40	M 39 x 3	28	23,0	92

type	l ₁ min	l ₂ min	h	α [°]	load rating C ₀ [kN]	weight (kg)
GAR / GAL 40 UK-2RS	86	48	150	7	180,0	1,800

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3616060467652
Diam. intérieur	40 mm
Diam. extérieur	92 mm
Epaisseur	28 mm
Type	GE
Poids	1800 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1
Norme	Sans norme

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE