

# Rotule SI

## GIR12-UK-DURBAL - GIR12-UK-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/si/gir12-uk-durbal

### GIR12-UK



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]					
	d	G	B	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>4</sub>	
GIR 12 UK	12	M 12	10	8,0	34	17,5	22	

type	measurement [mm]				$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W				
GIR / GRL 12 UK	23	50	19		11	24,5	0,096

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493695
Diam. intérieur	12 mm
Diam. extérieur	34 mm
Épaisseur	10 mm
Type	SI
Poids	96 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE