

Rotule SI

GIR25-UK-2RS-DURBAL - GIR25-UK-2RS-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/gir25-uk-2rs-durbal>

GIR25-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq 35$ with additional seal on both sides upon request.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free



order number	measurement [mm]	
right hand thread	left hand thread	
GIR 25 UK (-2RS)	25	M 24 x 2
	20	17,0
	64	33,5
	42	

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	t_2 min	h	W			
GIR / GRL 25 UK	48	94	36	7	83,0	0,640

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493961
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	64 mm
Diam. extérieur	2.52" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Type	SI
Poids	640 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE