

Rotule SI

GIR25-UK-2RS-DURBAL - GIR25-UK-2RS-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/gir25-uk-2rs-durbal>

GIR25-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 35$ with additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	C ₂	d ₂	d ₄
GIR 25 UK (-2RS)		25	M 24 x 2	20	17,0	64	33,5	42
type	measurement [mm]			α	load rating	weight		
	l ₃ min	h	W	°	C ₀ [kN]	[kg]		
GIR / GRL 25 UK	48	94	36	7	83,0	0,640		

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493961
Diam. intérieur	25 mm
Diam. extérieur	64 mm
Épaisseur	20 mm
Type	SI
Poids	640 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE