

Rotule SA POSL8-DURBAL - POSL8-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/posl8-durbal>

POSL8



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread: maintenance free, according to DIN ISO 12240-4, series K

Rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required

order number	measurement [mm]		B	C1	d2
	d	G			
right hand thread	8	M 8	12	9,00	22
left hand thread					
POSL 8					

type	measurement [mm]		alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	h			
POS / POSL 8	25	42	14	11,6	0,030

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494456
Diam. intérieur	8 mm
Diam. extérieur	22 mm
Epaisseur	12 mm
Type	SA
Poids	30 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	-
Norme	Sans norme

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE