

Rotule SI

SIZJL6-DURBAL - SIZJL6-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/sizjl6-durbal>

SIZJL6



female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / steel. Size 9 with grease nipple can be mounted upon request.

Rod end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: rod end body pressed around inner ring

Lubrication: lubrication required

order number	right hand thread	left hand thread	measurement [mm]						
			d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJL 6			6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91

type	inches	h ₁ min	measurement [mm]		h	α	load rating C ₀ [kN]	weight [g]
			W			[°]		
SIZJ / SIZJL 6	1 / 4 "	15,88	9,53		33,32	13,5	9,6	0,023

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952496702
Diam. intérieur	6.35 mm
Diam. extérieur	19.05 mm
Epaisseur	9.53 mm
Type	SI
Poids	23 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE