

Rotule GE
SIL6-E-DURBAL - SIL6-E-DURBAL
<https://www.123roulement.ch/roulement-palier/rotule/ge/sil6-e-durbal>

SIL6-E



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		right hand thread		left hand thread		measurement (mm)					
SI / SIL 6 E		d	G	B	C ₁	d ₂	d ₃	d ₄			
SI / SIL 6 E		6	M 6	6	4,4	21	10,0	13			

type	measurement (mm)			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₂ min	W	h			
SI / SIL 6 E	11	11	30	13	8,2	0,021

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3616060467881
Diam. intérieur	6 mm
Diam. extérieur	21 mm
Epaisseur	6 mm
Type	GE
Poids	21 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE