

Rotule SI

SI20-ES-2RS-DURBAL - SI20-ES-2RS-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/si20-es-2rs-durbal>

SI20-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number	right hand thread	left hand thread	d	G	measurement [mm]				d2	d3	d4
SI 20 ES (-2RS)			20	M 20 x 1.5	16	13,0	53	27,5	35		

type	l1 min	measurement [mm]		h	alpha [°]	load rating C0 [kN]	weight [kg]
SI / SIL 20 ES (-2RS)	40	32	77	9	9	60,0	0,35

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497105
Diam. intérieur	20 mm
Diam. intérieur	0.787" inch
Diam. extérieur	53 mm
Diam. extérieur	2.087" inch
Epaisseur	16 mm
Epaisseur	0.63" inch
Type	SI
Poids	350 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE