

Rotule SI SI20-ES-DURBAL - SI20-ES-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/si20-es-durbal>

SI20-ES



female thread; lubrication required, according to DIN ISO 12240-4; serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 20 ES			20	M 20 x 1.5	16	13,0	53	27,5	35

type	l ₁ min	W	h	α	load rating C ₀ (kN)	weight (kg)
SI / SIL 20 ES	40	32	77	9	60,0	0,35

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497112
Diam. intérieur	20 mm
Diam. extérieur	53 mm
Epaisseur	16 mm
Type	SI
Poids	350 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE