

## Rotule SI

### SIL25-ES-DURBAL - SIL25-ES-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/si/sil25-es-durbal

#### SIL25-ES



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSL...ES-2RS with additional seals also available.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

order number	right hand thread	left hand thread	d	G	measurement [mm]				d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SIL 25 ES			25	M 24 x 2	20	17,0	64	33,5	42		

type	l <sub>1</sub> min	measurement [mm]		h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SI / SIL 25 ES	48	36	94	7		83,0	0,64

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497150
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	64 mm
Diam. extérieur	2.52" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Type	SI
Poids	640 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE