

Rotule SI  
SIL30-ES-DURBAL - SIL30-ES-DURBAL  
<https://www.123roulement.ch/roulement-palier/rotule/si/sil30-es-durbal>

SIL30-ES

female thread:  
lubrication  
required,  
according to  
DIN ISO 12240-4:  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication required

| order number      |                  | measurement (mm) |          |    |      |    |      |    |
|-------------------|------------------|------------------|----------|----|------|----|------|----|
| right hand thread | left hand thread | d                | G        | B  | C1   | d2 | d3   | d4 |
| SIL 30 ES         |                  | 30               | M 30 x 2 | 22 | 19,0 | 73 | 40,0 | 50 |

| type           | measurement (mm) |    |     | load rating<br>C0<br>[kN] | weight<br>[kg] |      |
|----------------|------------------|----|-----|---------------------------|----------------|------|
|                | l2 min           | W  | h   |                           |                |      |
| SI / SIL 30 ES | 56               | 41 | 110 | 6                         | 110,0          | 0,93 |

CARACTÉRISTIQUES PRODUIT

|                 |                   |
|-----------------|-------------------|
| Marque          | DURBAL            |
| N° Ean13        | 3663952497266     |
| Diam. intérieur | 30 mm             |
| Diam. extérieur | 73 mm             |
| Epaisseur       | 22 mm             |
| Type            | SI                |
| Poids           | 930 g             |
| Filetage        | Filetage à gauche |
| Lubrification   | avec              |
| Conditionnement | 1                 |

[contact@123roulement.ch](mailto:contact@123roulement.ch)  
+33 359 36 04 90  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE