

Rotule SI
SIL60-ES-2RS-DURBAL - SIL60-ES-2RS-DURBAL
<https://www.123roulement.ch/roulement-palier/rotule/si/sil60-es-2rs-durbal>

SIL60-ES-2RS

female thread:
lubrication
required,
according to
DIN ISO 12240-4:
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number right hand thread	d	G	measurement (mm)				
			B	C1	d2	d3	d4
SIL 60 ES (-2RS)	60	M 52 x 3	44	38,0	135	70,0	88

type	measurement (mm)			load rating C0 [kN]	weight [kg]	
	l1 min	W	h			
SI / SIL 60 ES (-2RS)	70	75	175	6	450,0	5,5

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497624
Diam. intérieur	60 mm
Diam. extérieur	135 mm
Epaisseur	44 mm
Type	SI
Poids	5500 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE