

# Rotule SI

## SIL60-ES-DURBAL - SIL60-ES-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/si/sil60-es-durbal

### SIL60-ES



**female thread; lubrication required, according to DIN ISO 12240-4; serie E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSL...ES-2RS with additional seals also available.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 60 ES		60	M 52 x 3

type	measurement [mm]			load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h		
SI / SIL 60 ES	70	75	175	450,0	5,5

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497631
Diam. intérieur	60 mm
Diam. extérieur	135 mm
Epaisseur	44 mm
Type	SI
Poids	5500 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE