

Rotule SA SA20-ES-DURBAL - SA20-ES-DURBAL

https://www.123roulement.ch/roulement-palier/rotule/sa/sa20-es-durbal

SA20-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 20 ES		20	M 20 x 1,5	16	13,0	53

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 20 ES	43	27	78		9	60,0	0,310

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952498188
Diam. intérieur	20 mm
Diam. intérieur	0.787" inch
Diam. extérieur	53 mm
Diam. extérieur	2.087" inch
Epaisseur	16 mm
Epaisseur	0.63" inch
Type	SA
Poids	310 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE