

Rotule TAPR GIHO-K-25DO-DURBAL - GIHO-K-25DO-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/tapr/giho-k-25do-durbal>

GIHO-K-25DO

Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₃	d ₄	B	C ₁	C ₂	
GIHO-K 25 DO		25	29,3	65	M 16 x 1,5	30	62	20	17	17	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂				
GIHO-K / GIHO-KL 25 DO	68	23	100,5	30	7	67,0	0,67

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500737
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	65 mm
Diam. extérieur	2.559" inch
Epaisseur	17 mm
Epaisseur	0.669" inch
Type	TAPR
Poids	670 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE