

Rotule TAPR GIHO-K-40DO-DURBAL - GIHO-K-40DO-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/tapr/giho-k-40do-durbal>

GIHO-K-40DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-K 40 DO		
	d	d ₁ d ₂
	40	45,0 100
	G	M 27 x 2
	d ₄	45
	B	90
	C ₁	28
	C ₂	23
	C ₃	23

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂			
GIHN-K / GIHN-KL 40 DO	105	37	155,0	45	7	156,0
						2,16

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500812
Diam. intérieur	40 mm
Diam. extérieur	100 mm
Épaisseur	23 mm
Type	TAPR
Poids	2160 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE