


Rotule TAPR GIHO-KL-50DO-DURBAL - GIHO-KL-50DO-DURBAL


<https://www.123roulement.ch/roulement-palier/rotule/tapr/giho-kl-50do-durbal>


GIHO-KL-50DO

Female thread:
hydraulic rod ends,
according to
DIN 24555



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.





* without grease nipple

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₃	d ₄	B	C ₁	C ₂	
GIHO-KL	50 DO	50	56,0	120	M 33 x 2	55	105	35	30	30	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 50 DO	130	46	190,0	58	6	245,0	3,90

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500850
Diam. intérieur	50 mm
Diam. extérieur	120 mm
Epaisseur	30 mm
Type	TAPR
Poids	3900 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE