

# Rotule TAPR GIHO-KL-80DO-DURBAL - GIHO-KL-80DO-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/tapr/giho-kl-80do-durbal>

## GIHO-KL-80DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
			d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>
GIHO-KL 80 DO			80	89,4	205	M 48 x 2	90	156	55	47	47

type	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]	
GIHN-K / GIHN-KL 80 DO	185	64	287,5	82	6	585,0	15,00

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500935
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	205 mm
Diam. extérieur	8.071" inch
Epaisseur	47 mm
Epaisseur	1.85" inch
Type	TAPR
Poids	15000 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE