

Rotule TAPR GIHO-KL-100DO-DURBAL - GIHO-KL-100DO-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/tapr/giho-kl-100do-durbal>

GIHO-KL-100DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
			d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂
GIHQ-KL 100 DO			100	109,5	240	M 64 x 3	110	190	70	55	55

type	h ₁	l ₁	l ₂	l ₃	α [°]	load rating C ₀ [kN]	weight [kg]
GIHQ-K / GIHQ-KL 100 DO	240	86	360,0	116	6	865,0	27,30

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500966
Diam. intérieur	100 mm
Diam. extérieur	240 mm
Epaisseur	55 mm
Type	TAPR
Poids	27300 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE