

Rotule SI

BRF14-00-502-DURBAL - BRF14-00-502-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/si/brf14-00-502-durbal>

BRF14-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI.

inner ring:
ball bearing steel, hardened, superfinished.


lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 30)


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K



order number		measurements [mm]												
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	d ₈	l ₁	l ₂	l ₃	h	
BRF 14 -00	-502	14	20,0	M 14	17,0	36	25	19	13,5	57				
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating						
type	l	l ₁	l ₂	SW	α [°]	β [g]	Y	Y ₀	n _{max} [min ⁻¹]	C [N]	C ₀ [N]	stat.	stat.	
BRF 14	25	8,0	20	22	6,0	0,160	2,36	2,48	1025	5600	2000			

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507231
Diam. intérieur	14 mm
Diam. extérieur	36 mm
Épaisseur	19 mm
Type	SI
Poids	160 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE