

Rotule SA PM06-02-501-DURBAL - PM06-02-501-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/pm06-02-501-durbal>

PM06-02-501



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating	
type	approx. weight [kg]	d ₁	d ₂	d ₄	d ₅	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	C ₀ [N]
PM 06 -02 -501		6	M 10 x 1	8,5	24	1,28	1,34	1300	2445	765	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507491
Diam. intérieur	6 mm
Diam. intérieur	0.236" inch
Diam. extérieur	24 mm
Diam. extérieur	0.945" inch
Epaisseur	14 mm
Epaisseur	0.551" inch
Type	SA
Poids	57 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE