

Rotule SA PM10-00-502-DURBAL - PM10-00-502-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/pm10-00-502-durbal>

PM10-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating			
type	specification	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	C	C ₀
PM 10 -00	-502	10	M 14 x 1,5	13,5	36	19	20	14					
type		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'			
PM 10		49,5	28	82	2,5	2,5	9,5	0,168	1,69	1,77	1100	5120	1905

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507552
Diam. intérieur	10 mm
Diam. extérieur	36 mm
Epaisseur	20 mm
Type	-
Poids	168 g
Filetage	-
Lubrification	-
Conditionnement	-

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE