

Rotule SA PM15-00-502-DURBAL - PM15-00-502-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/pm15-00-502-durbal>

PM15-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating	
type	specification	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀ [N]
PM 15 -00	-502	15	M 20 x 1,5	18,5	42	26	20	14					
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	α' [°]	weight [kg]	rotational speed limit [min ⁻¹]	basic load rating C [N]	basic load rating C ₀ [N]
PM 15	62,5	30	100	3,0	2,5	6,5	0,310	2,07	2,17		975	5485	3270

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507637
Diam. intérieur	15 mm
Diam. intérieur	0.591" inch
Diam. extérieur	42 mm
Diam. extérieur	1.654" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Type	SA
Poids	310 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE